

## Description & application

**CLA-252** is a multi-purpose degreaser that is recommended for various open plant cleaning applications in the food industry.

**CLA-252**'s synergistic combination of surfactants removes efficiently different types of organic food soils either from plant or animal origin, in addition to lubricating oils and greases.

**CLA-252** can be used on all installations, equipment and tools used in the food industry, including our MicroDry<sup>®</sup> lubrication solutions.

**CLA-252** is also very efficient for floor and wall cleaning in processing areas.

Only for professional use.

## Use instructions

**CLA-252** is used for foaming/rinsing the surfaces to be cleaned to remove oil substances and spillages of food/beverage.

Apply as following:

- **Foam units and professional floor scrubbers:** 1% - 5% between 20°C and 55°C
- **Manual applications:** 1% - 5% between 15°C and 40°C

After a contact time of at least 15 minutes rinse thoroughly after use (within 1 hour) and ensure that all product residues and soil particles are removed.

## Product characteristics

|             |  |
|-------------|--|
| Composition | Contains anionic and nonionic surfactants, solvent, phosphonates, polycarboxylates |
| Appearance  | Clear liquid   |
| Colour      | Pale yellow  |
| Odour       | Characteristic   |
| pH (1%)     | ± 10,4   |
| Density     | ± 1,03 kg/L  |
| Solubility  | Miscible in water in all proportions   |

## Materials compatibility

When **CLA-252** is used according to the recommended use instructions, then **CLA-252** can be used on materials commonly used in the food and beverage industry.

## Environment

Surfactants used in **CLA-252** comply with the European regulation EU648/2004 on the biodegradability of surfactants.

## Safety

Never mix **CLA-252** with other products. Carefully read the material safety data sheet of **CLA-252** and follow the chemical handling and disposal guidance.

## Storage

Store **CLA-252** in its original packaging between 5°C and 30°C. Avoid exposure to direct sunlight.

## Packaging

Common unit package: 20 L drum – gross weight 21,46 kg

Common shipment package: pallet with 2 layers of 12 drums/layer – H1070mm x I 800 mm x L 1200 mm.