




Recommendations

- Before starting, perform a test in order to determine the desired colour of the mortar. Adjust the amount of dyes correspondingly.
- Once the dyeing ratio has been determined, always apply the same ratio dyes/water as well as the blending time in order to avoid differences in colour.



Application condition

Application temperature: from +5°C till +30°C.



Directions for use

- Disperse the dyes and mix them dry with the cement.
- Add the mixing water to the mortar and mix it until mortar with a homogeneous colour is obtained.



Available in	0,75 kg	4 kg	20 kg	25 kg
Black	x	x		x
Red	x	x		x
Brown	x	x		x
Green		x		x
White		x		x
Ochre		x	x	
Beige		x		x

Mixing ratio	Consumption	Packaging
Undiluted	± 7 to 10 % on cement weight	0,75 kg (18 pcs/cardboard box: red, black, brown) 4 kg and 25 kg
Colours		Application temperature
Red, black, green, white, brown & ochre		+ 5°C till + 30°C

As the applications of our products are diverse, no single application guideline can be laid down. All product data reflect the state of knowledge of our products at the time of publication. Therefore all suggestions and recommendations concerning the use of our products are merely illustrative. Apply the product on a small and insignificant spot before starting to use our products to be sure the desired result is obtained. Always ask for the technical sheet of our products. Visit the website www.compaktuna.be. Consult our "technical department" which can be reached for free on the green number 0800/92279. The Dutch text shall be exclusively binding.