

P.T.B.-CEMENT

ϵ

AALBORG PORLAND A/S Rørdalvej 44, P.O. Box 165 9300 Aalborg Denmark

0615-CPR-9806 PORTLAND CEMENT CEM I 52,5R SR5 EN 197-1

Preparation of cement, mortar, grout etc.
The declared performance, DOP 9806/01-DOP.

ϵ

S.A. Cimenteries CBR Cementbedrijven N.V.

Chaussée de la Hulpe 185 Therhulpsesteenweg 185 B-1170 BRUSSELS

0965-CPR-C0026 PORTLAND CEMENT CEM I 52,5N EN 197-1

Preparation of concrete, mortar, grout, etc. The declared performance, by levels and classes is defined by the cement designation.

Hydraulic binder





Characteristics

P.T.B.-CEMENT is a cement based on the Portland clinker.

- Grey: CEM I 52,5 N, is a Portland cement consisting of 95-100% cement clinker. The compressive strength after 28 days on normalized mortar following EN 197-1 (water/ cement factor = 0,5) is at least 52,5 MPa.
- White: CEM I 52,5 R SR5. The compressive strength after 28 days on normalized mortar following EN 197-1 (water/cementfactor = 0,5) is at least 52,5 MPa.



Packaging






P.T.B.-CEMENT is packed in bags of 5 kg. P.T.B.-CEMENT can be kept for 6 months in the original, unopened packaging when stored in a dry place.













P.T.B.-COMPAKTUNA®