

MB 1000: MB Hydraulic Breakers for carriers from 12 up to 21 t weight

3363 9887 85


[PDF-bestand maken](#)
[Informatie aanvragen](#)

Contact

[Stuur ons een e-mail](#)

Snelkoppelingen

[Atlas Copco Print Shop](#)
[Atlas Copco Multimedia Gallery](#)
[Product - informatie](#)
[Foto's en video's](#)

Atlas Copco's range of medium-duty hydraulic breakers was developed for a wide variety of applications. The combined gas/oil power principle means they are both powerful and highly flexible with regard to oil flow rate and pressure. Their technically advanced percussion mechanism, e.g. with long piston stroke, reduce unavoidable vibrations far more efficiently than many other makes.

Kenmerken en voordelen

- VibroSilenced Plus system
- ContiLube II
- AutoStart
- AutoControl
- Energy recovery
- Percussion chamber ventilation

Applications

- Demolition
- Foundation work
- Tunneling
- Trenching
- Underwater work
- Boulder size reduction in quarries

Technische gegevens

 Eenheden: **Metrisch** [Engels](#)

Technische gegevens	
Gewichtsklasse voertuig	12 - 21 t
Service weight **	1000 kg
Oliedebiet	85 - 130 l/min
Operating pressure	160 - 180 bar
Slagsnelheid	350 - 750 blows/min
Working tool diameter	110 mm
Working length of tool	570 mm
Max. opgenomen hydraulisch vermogen	39 kW
Sound power level guaranteed ***	119 dB(A)
Sound pressure level (r=10m) ***	90 dB(A)

Productweergaven

