

INDUSTRIAL VACUUM CLEANERS

W 2 Infini T - INDUSTRIAL THREE PHASE



FOOD INDUSTRY



CHEMICAL-PHARMACEUTICAL



CLEANING CONTRACTORS



- ✓ Detachable container with direct bagging option.
- ✓ Filter with wide filtration surface for fine dusts, with integrated manual cleaning system.
- ✓ Compact industrial vacuum cleaner with side channel blower, ideal for continuous service and maintenance free.
- ✓ Suitable for simultaneous suction of dusts, liquids and solids.



SUCTION UNIT

Voltage	V - Hz	400 - 50
Power	kW	1,8
Max waterlift	mmH ₂ O	2.300
Max air flow	m ³ /h	250
Suction inlet	mm	50



FILTER UNIT

Filter Type		Star
Surface - Diameter	cm ² -mm	20.000 - 420
Material - Efficiency	IEC 60335-2-69	Polyester - L
Air load on filter	m ³ /m ² /h	125
Cleaning system		Manual



COLLECTION UNIT

Collection tank		Steel
Discharge system		Roll-out container
Capacity	lt.	40



VOLUME

Dimensions	cm	55 x 63 x 130h
------------	----	----------------



SUCTION UNIT

Suction is developed by a powerful side channel blower with direct coupling between the fan and the motor and no transmission system, making it completely maintenance free and fit for continuous duty.



FILTER UNIT

A polyester pocket filter inside the steel filter chamber protects the suction system. A filter shaking lever allows easy cleaning for longer lasting filter life.



COLLECTION UNIT

Suctioned material deposits inside a detachable steel container fitted with wheels, allowing easy and clean emptying of the suctioned material. Use with disposable bags is possible.



OPTIONALS

- ✓ Nomex heat resistant filter up to 250°
- ✓ Absolute Hepa filter H14
- ✓ Accessory basket
- ✓ Class M filter
- ✓ PTFE coated class M filter
- ✓ Class M teflon hydro-oleophobic filter
- ✓ Antistatic class L filter
- ✓ Stainless steel collection tank
- ✓ Stainless steel collection tank and filter chamber
- ✓ Earth grounding
- ✓ Pressure relief valve

filter-technics

Technical Customer Support

T: +32 3 254 05 67

E: info@filter-technics.be

