



Product data
Floorify® Rigid Vinyl Planks & Tiles
click

version: 1/07/2018



EN

Parameter Norm Performance






Dimensions and basic data











		Planks	
Width:	ISO24337	178	mm
Length:	ISO24337	1219	mm
Number of panels per pack:		12	pc
m ² per pack:		2,6	m ²
Weight per pack:	ISO23997	19,9	kg
Total thickness:	ISO24337	4	mm
Top Layer thickness:	EN429	0,4	mm
Core:		Sound reducing, robust and waterproof Floorify® Rigid Core	
Finish:		Protected with scratch & stain resistant Floorify® Quiet Sense Technology	
Locking method:		Traditional glueless click under license of Unilin.	

Warranty



	Usage class:	ISO10582	32
	CE:	EN 14041	DoP FF001
	Warranty:	Residential use:	20 years

Technical data

		Norm Requirements	Floorify values	
	Wear resistance:	EN13329, Annex E	≥2000 cycles	≥3000 cycles - AC3
	Impact resistance:	EN13329	≥ 1 200 mm	In combination with Floorify® Comfort underlay: 1800mm - IC3
	Residual indentation:	ISO24343-1	≤ 0,2 mm	In combination with Floorify® Comfort underlay: no visible changes
	Stain resistance:	EN423	Groups 1 and 2: grade 5; Group 3: grade 4	Groups 1, 2 and 3: grade 5;
	UV resistance:	ISO 105-B02:1994, Method 3a	6 minimum	>6

	Fire classification:	EN 13501-1 ISO 9239-1	Bfl-s1	
	Dimensional stability:	EN ISO23999 6uur bij 80C	≤ 0,25 %	≤ 0,10 %
	Locking strength:	ISO24334	Long side: >1kN/m side: 1,5kN/m	Short Long side: >4,5kN/m Short side: >4,5kN/m
	Displacement of furniture feet:	EN424	Foot 0,1mm / 32kg	No changes
	Castor chairs:	EN425	>25000 cycles: No delamination, no disturbance	No visible changes
	Slip resistance:	EN13893 DIN 51130:2014	DS R10	
	Swelling:	ISO24336	<18%	0%
	Thermal resistance (floor + underlay):	EN12667	<0,15R (m²K/W)	0,0660R (m²K/W) (0,012 Floor + 0,0540 Comfort Underlay)
	Floor heating:	Appropriate for all standard heating systems IN cement flooring. NOT appropriate for heating films.		
	Impact sound improvement:	ISO712	ΔLw18Db	In combination with Floorify® Comfort underlay: Δ Lw20Db

Dangerous Substances

	Formaldehyde emission:	EN14041	E1	
	TVOC 28 days:	<1000µg/m³	<10µg/m³	
	Emissions in the interior air:)	A+	
	REACH:	Floorify® floors and accessories are fully REACH compliant		
	Plasticizers:	DOPT - virgin PVC - 100% orthophtalate free		

Floorify NV reserves the right to make alterations to material and structures when this serves to improve the quality