



# Technical data sheet

PROTECTION MADE EASY

---

## Aquathinner

---

### Description and destination of the product

---

**Aquathinner** is a mixture of solvents and water, especially formulated for a slower drying and improvement of the open time and flow of water thinnable lacquers. Especially when the ambient temperature is high and the open time of the paint is an important factor, **Aquathinner** gives a longer application time.

### Technical data

---

○ **Density:** Density: 1.02 (± 0.02) g/ml

### Use

---

**Aquathinner** can be added to all water thinnable lacquers, such as **Satilux Aqua** and **Resoprim Aqua**.

Maximum recommended dose: up to 2 %.

Overdosing can lead to a higher risk of sags and a higher water sensitivity of the paint.

### Storage stability

---

Minimum 3 years in the original, unopened packing, stored in a frost-free environment at temperatures between +5°C and +40°C.

### Safety measure

---

For detailed information about safety measures, personal protection and transport data of this product, we refer to the safety data sheet.

*The last update of our technical data sheets is always available at our website: [www.libertpaints.com](http://www.libertpaints.com)*

#### Disclaimer

*The information given in this technical data sheet is only a general product description, based on our experiences and tests and therefore does not represent a specific practical case. Consequently Libert Paints doesn't guarantee the functionality or result and takes no responsibility in this respect.*

*We advise our clients to test the applicability of the product to the nature and the state of the surfaces and to carry out the necessary representative tests in case of doubt. Please contact our R&D department as the occasion arises.*

*Attention: our clients should verify whether the present technical data sheet hasn't been replaced by a more recent version.*